# 2NB



## **REVOV STAR** 51.2V 200Ah 5kVa/10.2kWh

C

#### **KEY FEATURES**

- UPS (uninterruptible power supply) for backup for essential circuits in home and office.
- Pre-programmed, all-in-one, kit-pack contains everything a qualified installer would require to get a home or a small business up and running with a UPS 5kVA/10.2kWh, fully enclosed and protected unit.
- Cost effective solution with a rapid installation time.
- Supplies AC power pure Sine Wave AC Output seamless backup transition.
- Fast charging from grid (or solar).
- LCD Display Battery charge info display.
- Optional remote monitoring function.
- Note: This unit is not IP rated so the unit must reside indoors.

## FREEDOM FROM DEPENDENCE

WWW.REVOV.CO.ZA

The **REVOV STAR** is a 10.2kWh residential or small business backup power unit. This fully integrated backup system includes preprogrammed batteries, BMS and inverter, making it a quick installation.

The complete DC system stores energy, detects grid status, and automatically supplies your home when the national grid is compromised. Unlike generators, the **REVOV STAR** requires no maintenance or fuel, creates no fumes and is very quiet. Power can be stored from Solar or from Grid.

The batteries have a 16-cell configuration for long life and the flexibility to expand capacity by adding extra units, or to connect one **REVOV STAR** per phase. **Note:** The distribution board of the home will need attention by a qualified electrician, to sort into Essential and Non-Essential circuits and accompanying protection e.g. AC breakers.

### WARRANTY

**REVOV Batteries (PTY) LTD:** 10 years or 3 500 cycles at 1 cycle per day. Warranty for inverter depends on brand used in the STAR.

**DOD** When used properly every day the STAR can be safely discharged to 100% of its rated 200Ah capacity. Battery life is shortened if it is discharged beyond its rated Ah capacity.

# 



### **BMS FUNCTION**

- Cell and battery voltage detection.
- RS485 communication interface.
- Battery charge and discharge control (MOSFET).
- Cell, ambient and MOSFET temperature detection.
- Display of the Battery capacity and number of cycles.
- Cells balancing Equalization of single cells intelligently.
- Watchdog protection for circuits to ensure safe operation.

#### **SPECIFICATIONS**

Nominal Voltage DC	51.2V	
Energy Capacity	10.2kWh	
Charge current	60A	
Recommended Recharge	4hours at 50A	
Single Phase AC Output	220 - 240V AC	
Depth of Discharge	100%	
Round Trip Efficiency	90%	
Max Power - continuous	5kW	
Unit Size: L x W x D	1950mm x 550mm x 300mm	
Battery Size: Length x Width x Height (mm)	520 x 442 x 170	
Battery Weight	53kg each	
In-line Parallel Connect Up to 6 REVOV STARS		

### NOMINAL SPECIFICATIONS

	Matched Pair
Nominal Voltage	51.2 (25.6V x 2)
Capacity (C/2) (Ah)	200
Energy (C/2) (kWh)	10.2
Maintenance	Charge the battery every 6 months when in storage

### **OPERATING CONDITIONS**

Designed Cycle Life + 25°C	7000+ cycles
Operating Temperature	0~45°C
Transport regulation compliance	UN3480
Storage temperature	Short term storage: -10°C~+45°C (<3 months, SOC: 20%~60%) Long term storage: -10°C~+40°C (< 1 year, SOC: 30%~60%)
EMC standard compliancea	EN 61000 chapter 4.2, 4.3, 4.5, 4.6/EN55022
Certificate	TUV SUD/CE UL1642/ UN38.3
Protection class	IP20



Enquiries: enquiries@revov.co.za Enquiries: 010 035 6061 WhatsApp: +27 (0)73 159 5938

Technical Service Desk: 010 035 0680 Technical Service Email: admin@revov.co.za Unit 1, Cranberry Industrial Park, 1486 Cranberry Street Honeydew, Roodepoort, 2040, **GPS:** 2604'46.9"S 2755'31.7"E

