



Store Energy, Save The Planet



Address: A9, Software new city 2, 156# Tiangu 8th road,
High-tech zone, Xi'an, Shaanxi, China, 710065
Tel: +86 029 89540338 | **Mobile:** +86 176 9134 2988
Email: sales@dyness.net | **Web:** www.dyness.net

Dyness Battery

LiFePO4 Energy Storage System



COMPANY PROFILE

The growing popularity of solar rooftop installation on residential and commercial building is increasing interest in batteries that could store electricity from those installations.

Such battery storage systems could benefit homeowners, by giving them more control over how and when they obtain the power they need, while helping utilities to regulate the peak and frequency by shifting demand to off-peak hours and smoothing out the load on the system.

R&D Center · Xi'an City



About Dyness

Dyness owns the professional team with top class experts in the battery storage industry. All products in our company are produced according to international standards, and passed TUV / CE / EN62619 / UN38.3 / IEC62040 testing issues. We also formed a joint laboratory with Shaanxi Normal University, focusing on power battery research and development.

Our energy storage system stores excess power produced from solar in daytime, it can be used at night to increase greater energy self-sufficiency and security, or used at peak time to reduce household electric charges. Our battery is suitable for existing solar PV systems, also easy to be installed with new solar systems.

We, Dyness devote ourselves to responsible engineering of the safest, greenest possible future for you and your family. We have launched our latest Battery Energy Storage System (BESS) Powerbox to Australia, South-America, Africa, Europe with moderate price and top class quality.

Let's start using the sunshine by schedule!



Dyness B4850

Battery module

Intelligent

Safe

Modular



【Intelligent】

- Each module is equipped with an independent BMS system

【Compact design】

- Weight/Kg 22
- Size/mm 480 * 360 * 90
- Practical pull ear design improves operation convenience

【Safe】

- Safe lithium iron phosphate battery cell
- Compact size ultralight module

【Intelligent management】

- Dyness is equipped with intelligent BMS for each battery pack to manage modules effectively.
- Compared with the traditional module, B4850 can meet the capacity storage and greatly enhance the cycle life.

【Application】

- The Dyness battery B4850 module is widely used in energy storage and electrical products. Household energy storage systems; Centralized power station energy storage system.

Intelligent · Safe · Modular



SPECIFICATION

Model	B4850
Battery Type	LiFePO4
Nominal Battery Energy	2.4kWh
Nominal Capacity	50Ah
Nominal Voltage	48V
Charging Cut-off vol.	54V
Discharging End-off vol.	42V
Recommend C Rate	0.5C
Continuous Max C Rate	1C
Net Weight	22Kg
Dimension [W*D*H]	480*360*90mm
Charging Temp. Range	0 ~ 50°C
Discharging Temp. Range	-20 ~ 50°C
Calendar Life ^[1]	6000 Cycles
Protection Level	IP20
Communication	CAN / RS485 / DRY CONTACT
Certification & Safety Standard	TUV/CE/EN62619/IEC62040/UN38.3/CEC Accredited
Warranty	10 Years

[1] Test conditions: 0.2C Charging/Discharging, @25°C, 80% DOD

B3



Features and advantages

- LiFePO4 battery, Safe, Longer life span
- Modular design, Easy to stack, Quick installation
- Larger energy capacity
- Natural cooling with optional heat/fan configuration
- Wide temperature range of -20~50°C



SPECIFICATION

Model	B3
Nominal Energy	3.6kWh
Nominal Capacity	75Ah
Nominal Voltage	48V
Max. Continuous Discharge Current	50A
Max. Continuous Charge Current	50A
Charging Cut-Off Vol.	54V
Discharging End-Off Vol.	42V
Net Weight	30Kg
Dimension[W*D*H]	480*380*130mm
Protection Level	IP20
Calendar Life ^[1]	6000 Cycles
Charging Temperature Range	0~50°C
Discharging Temperature Range	-20~50°C
Communication	CAN / RS485
Configuration	40 modules parallel at most
Recommend C Rate	0.5C
Warranty	10 years

[1] Test conditions: 0.2C Charging/Discharging, @25°C, 80%Dod

B48 100



Features and advantages

- LiFePO4 battery, Safe, Longer life span
- Modular design, Easy to stack, Quick installation
- Larger energy capacity
- Natural cooling with optional heat/fan configuration
- Wide temperature range of -20~50°C



SPECIFICATION

Model	B48100
Module Type	LFP
Total storing Energy[kWh]	4.8
Voltage Range[Vdc]	42~54
Battery Voltage[Vdc]	48
Battery Capacity[Ah]	100
Battery System Charge Voltage[Vdc]	54
Battery Working Current[A](Standard)	30
Battery Working Current[A](Normal)	50
Battery Working Current[A](Max)	100
Battery Discharge lower-Voltage[Vdc]	42
Discharge condition[°C]	-20~55
Charge condition[°C]	-5~55
Max. Discharge Power [kW]	4.32
Enclosure Protection (IP)	IP20
Size [mm]	481*405*178
Weight [kg]	40Kg
Warranty	10 years

Dyness Powerbox

【Powerbox】

Adopts LiFePO4 chemistry battery with safety performance and long life time, which offers you four capacities to meet your more requirements.

TUV Certified · CEC Accredited · IP65 Protection · Flexible Expansion



Features and advantages

- Compact Size & Light Weight
- High Power Output & Usable Energy Ratio
- Modular Design & Expandable System
- Safest Battery & Perfect Compatibility
- Natural cooling & Easy Installation
- Certifications Available



SPECIFICATION

Model	Powerbox
Battery Type	LiFePO4
Battery Module	F-10.0 4 Modules
Battery Capacity [Ah]	200
Nominal Battery Energy [kWh]	9.6
Max Output Power [kW]	4.8
Net Weight [Kg]	113
Dimension [H*W*D, mm]	928*555*210
Working Voltage [V]	42~54
Operating Temp. Range [°C]	-20~50
Calendar Life [Cycles] ^[1]	6000
Nominal Voltage [V]	48
Protection Level	IP65
Communication	CAN / RS485 / DRY CONTACT
Certification & Safety Standard	TUV/CE/EN62619/IEC62040/UN38.3/CEC Accredited
Scalability [kWh]	Up to 4 units to parallel
Compatible Inverters	Goodwe Victron Imeon Solis Luxpower Growatt GMDE Sofar Voltronic Deye More brands will be announced
Warranty	10 Years
Warranty Document Supplied	Yes
Color	White
Alarms	Overcharge Overdischarge Overcurrent Overtemperature Short Circuit
Pros	Can be used in both off-grid and hybrid setups, compact design, modular expansion
Monitoring & Protection	Each module has BMS, breaker embedded in system

[1] Test conditions: 0.2C Charging/Discharging, @25°C, 80% DOD

Power Depot



Features and advantages

- Safest LiFePO4 rechargeable battery
- Higher usable energy ratio, less self consumption
- 1/3 weight of equivalent capacity Lead-Acid battery
- Plug and Play, quick installation, up to 3 unit parallel
- Wide temperature range of -20~50°C
- Contains no toxic heavy metals or caustic materials



SPECIFICATION

Model	PowerDepot
Battery Type	LiFePO4
Battery Module	H5
Battery Capacity [Ah]	100
Nominal Battery Energy [kWh]	4.8
Max Output Power [kW]	4.8
Net Weight [Kg]	65
Dimension [H*W*D, mm]	574*228*600
Working Voltage [V]	42~54
Operating Temp. Range [°C]	-20~50
Calendar Life [Cycles] ^[1]	6000
Nominal Voltage [V]	48
Protection Level	IP65
Communication	CAN / RS485 / DRY CONTACT
Certification & Safety Standard	CE / UN38.3
Scalability [kWh]	Up to 4 units to parallel
Compatible Inverters	Goodwe Victron Imeon Solis Luxpower Growatt GMDE Sofar Voltronic Deye More brands will be announced
Warranty	10 Years
Warranty Document Supplied	Yes
Color	White
Alarms	Overcharge Overdischarge Overcurrent Overtemperature Short Circuit
Pros	Can be used in both off-grid and hybrid setups, compact design, modular expansion
Monitoring & Protection	Each module has BMS, breaker embedded in system

[1] Test conditions: 0.2C Charging/Discharging, @25°C, 80% DoD

Dyness Powercube

Dyness Powercube is tailor made for larger residential and light commercial.
TUV Certified · CEC Accredited · IP65 Protection · Flexible Expansion



Features and advantages

- Compact Size & Light Weight
- High Power Output & Usable Energy Ratio
- Modular Design & Expandable System
- Safest Battery & Perfect Compatibility
- Natural cooling & Easy Installation
- Certifications Available



SPECIFICATION

Model	Powercube				
Battery Type	LiFePO4				
Battery Module	5 Modules	6 Modules	7 Modules	8 Modules	9 Modules
Battery Capacity [Ah]	250	300	350	400	450
Nominal Battery Energy [kWh]	12	14.4	16.8	19.2	21.6
Working Voltage [V]	42~54				
Operating Temp. Range [°C]	-20~50				
Calendar Life [Cycles] ^[1]	6000				
Nominal Voltage [V]	48				
Protection Level	IP65				
Communication	CAN / RS485 / DRY CONTACT				
Certification & Safety Standard	TUV/CE/EN62619/IEC62040/UN38.3/CEC Accredited				
Scalability [kWh]	Up to no limit				
Compatible Inverters	Goodwe Victron Imeon Solis Luxpower Growatt GMDE Sofar Voltronic Deye More brands will be announced				
Warranty	10 Years				
Warranty Document Supplied	Yes				
Color	White				
Alarms	Overcharge Overdischarge Overcurrent Overtemperature Short Circuit				
Pros	Can be used in both off-grid and hybrid setups, compact design, modular expansion				
Monitoring & Protection	Each module has BMS, breaker embedded in system				

[1] Test conditions: 0.2C Charging/Discharging, @25°C, 80% DOD

Dyness Tower

Safe and Reliable ▪ IP65 Protection ▪ Flexible Size ▪ Quick Installation



SPECIFICATION

Model	Tower T7	Tower T10	Tower T14	Tower T17	Tower T21
Usable Energy	7.10KWh	10.66KWh	14.20KWh	17.76KWh	21.31KWh
Nominal Capacity	37Ah	37Ah	37Ah	37Ah	37Ah
Nominal Voltage	192V	288V	384V	480V	576V
Maximum Continuous Discharge Power ^[2]	4.26KW	6.39KW	8.52KW	10.65KW	12.78KW
Maximum Continuous Charge Power ^[2]	4.26KW	6.39KW	8.52KW	10.65KW	12.78KW
Net Weight	105Kg	146Kg	187Kg	228Kg	269Kg
Dimension[W*D*H]	700*504*380mm	900*504*380mm	1100*504*380mm	1300*504*380mm	1500*504*380mm
Protection Level	IP54	IP54	IP54	IP54	IP54
Calendar Life ^[1]	6000 Cycles	6000 Cycles	6000 Cycles	6000 Cycles	6000 Cycles
Charging Temperature Range	0~50°C	0~50°C	0~50°C	0~50°C	0~50°C
Discharging Temperature Range	-10~50°C	-10~50°C	-10~50°C	-10~50°C	-10~50°C
Internal Battery Module	HV9637	HV9637	HV9637	HV9637	HV9637
Module Connection	series	series	series	series	series
Module Number	2	3	4	5	6
Communication	CAN	CAN	CAN	CAN	CAN
Warranty	10 Years	10 Years	10 Years	10 Years	10 Years
Compatible Inverter	Goodwe, Luxpower, more brands are under testing				
Certification	TUV/CE/IEC62619/IEC62040/UN38.3				

[1] Test conditions: 0.2C Charging/Discharging, @25°C, 80% Dod

[2] Maximum Continuous Discharge/Charge Power when communicate with inverter is 0.6C

Features and advantages

- Maximum safety performance with LFP technologies
- Built-in aluminum heat sink, optional heating solutions
- Compact design with flexible size options
- IP54 protection for indoor and outdoor use
- Compatible with leading inverter brands
- Black start function available, quick installation

