

Model	SUNSYNK-5K-SG01HP3-EU-AM2	SUNSYNK-6K-SG01HP3-EU-AM2	SUNSYNK-8K-SG01HP3-EU-AM2	SUNSYNK-10K-SG01HP3-EU-AM2	SUNSYNK-12K-SG01HP3-EU-AM2	SUNSYNK-15K-SG01HP3-EU-AM2	SUNSYNK-20K-SG01HP3-EU-AM2	SUNSYNK-25K-SG01HP3-EU-AM2
Battery Input Data								
Battery Type	Lithium-ion							
Battery Voltage Range (V)	160~700							
Max. Charging Current (A)	30		37				50	
Max. Discharging Current (A)	30		37				50	
Number of Battery Input	1							
Charging Strategy for Li-Ion Battery	Self-adaption to BMS							
PV String Input Data								
Max. DC Input Power (W)	6500	7800	10400	13000	15600	19500	26000	32500
Max. DC Input Voltage (V)	1000							
Start-up Voltage (V)	180							
MPPT Range (V)	150-850							
Full Load DC Voltage Range (V)	195-850	195-850	260-850	325-850	340-850	420-850	500-850	625-850
Rated DC Input Voltage (V)	600							
PV Input Current (A)	20+20				26+20		26+26	
Max. $PV_{I_{sc}}$ (A)	30+30				39+30		39+39	
No. of MPPT	2							
No. of Strings per MPPT	1+1				2+1		2+2	
AC Output Data								
Rated AC Output and UPS Power (W)	5000	6000	8000	10000	12000	15000	20000	25000
Max. AC Output Active Power (W)	5500	6600	8800	11000	13200	16500	22000	27500
AC Output Rated Current (A)	7.6/7.3	9.1/8.7	12.2/11.6	15.2/14.5	18.2/17.4	22.8/21.8	30.4/29	37.9/36.3
Max. AC Output Current (A)	8.4/8	10/9.6	13.4/12.8	16.7/16	20/19.2	25/24	33.4/31.9	41.7/39.9
Max. Three-phase Unbalanced Output Current(A)	13	13	18	22	25	30	35	41.7